

RESILIENT POLYURETHANE FLOOR COVERING

maximum total weight 3,4 kg/m²



The resilient floor covering based on polyurethane is produced with the reactive component castor oil as renewable raw material and with natural inorganic fill. Products are available in many different decors and textures, and it is offered as rolls or as planks.



Windmoeller Inc. is a subsidiary of Windmoeller GmbH, the innovative flooring designer and manufacturer headquartered in Augustdorf, Germany.

Founded in 1948, Windmüller is a third-generation family-owned company with a global presence in over 70 countries.

Fueled by pioneer thinking, we are committed to using our expertise and resources to make a positive impact on the planet.

We carefully select renewable resources, recycled materials, and environmentally friendly options to minimize our environmental impact. We prioritize reducing waste, energy, and our carbon footprint in every aspect of our production process. We have a culture of transparency, ensuring that our stakeholders have access to accurate and reliable information.

From the raw materials we choose and the energy we use, to the safety and lasting performance of our solutions, we take human and environmental health seriously.

Visit windmoellerinc.com for more information.



ENVIRONMENTAL PRODUCT DECLARATION



Windmoeller Inc.

Resilient polyurethane floor covering for adhesive bonding, maximum total weight 3,4 kg/m²

According to EN 15804 and ISO 14025

Dual Recognition by UL Environment and Institut Bauen und Umwelt e.V.

This declaration is an environmental product declaration (EPD) in accordance with ISO 14025. EPDs rely on Life Cycle Assessment (LCA) to provide information on a number of environmental impacts of products over their life cycle. **Exclusions:** EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc. **Accuracy of Results:** EPDs regularly rely on estimations of impacts, and the level of accuracy in estimation of effect differs for any particular product line and reported impact. **Comparability:** EPDs are not comparative assertions and are either not comparable or have limited comparability when they cover different life cycle stages, are based on different product category rules or are missing relevant environmental impacts. EPDs from different programs may not be comparable.



PROGRAM OPERATOR	UL Solutions
DECLARATION HOLDER	Windoeller Inc.
ULE DECLARATION NUMBER	4791591314.100.1
IBU DECLARATION NUMBER	EPD-WIN-20230577-CBA1-EN
DECLARED PRODUCT	Resilient Floor Covering
REFERENCE PCR	IBU Floor Coverings 2021

DATE OF ISSUE	April 4 th 2024
PERIOD OF VALIDITY	5 years

SCOPE	This EPD is Manufacturer Declaration (1a) – Declaration of a specific product from a manufacturer’s plant. The owner of the declaration shall be liable for the underlying information and evidence.
CONTENTS OF THE DECLARATION	Product definition Information about basic material and the material's origin Description of the product’s manufacture Indication of product processing Life cycle assessment results Testing results and verifications

The PCR review was conducted by:	IBU
	PCR Review Panel
	Info@ibu-epd.com

The CEN Norm EN 15804 serves as the core PCR. This declaration was independently verified in accordance with ISO 14025 by Underwriters Laboratories <input type="checkbox"/> INTERNAL <input checked="" type="checkbox"/> EXTERNAL	 Cooper McCollum, UL Solutions
---	-----------------------------------

This life cycle assessment was independently verified in accordance with ISO 14044 and the reference PCR by:	Independence Verifier - IBU
--	-----------------------------



ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	Windmüller GmbH
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-WIN-20230577-CBA1-EN
Issue date	04.04.2024
Valid to	03.04.2029

**Resilient polyurethane floor covering for adhesive bonding,
maximum total weight 3,4 kg/m²
Windmüller GmbH**

www.ibu-epd.com | <https://epd-online.com>



ECO PLATFORM

EPD
VERIFIED



General Information

Windmüller GmbH

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-WIN-20230577-CBA1-EN

This declaration is based on the product category rules:

Floor coverings, 01.08.2021
(PCR checked and approved by the SVR)

Issue date

04.04.2024

Valid to

03.04.2029



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

Resilient polyurethane floor covering for adhesive bonding, maximum total weight 3,4 kg/m²

Owner of the declaration

Windmüller GmbH
Nord-West-Ring 21
32832 Augustdorf
Germany

Declared product / declared unit

1 m² resilient floor covering 'PURLINE'

Scope:

The manufacturer declaration applies to products with a maximum total weight of 3,4 kg/m².
The product is available as rolls or planks. It is manufactured at the Windmüller GmbH site in Detmold, Germany. Cutting of planks takes place at the Windmüller GmbH site in Augustdorf, Germany.
The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
<input type="checkbox"/>	internally
<input checked="" type="checkbox"/>	externally



Angela Schindler,
(Independent verifier)

Product

Product description/Product definition

The resilient floor covering based on polyurethane is produced with the reactive component castor oil as renewable raw material and with natural inorganic filler. Products are available in many different decors and textures and it is offered as rolls or as planks. The declaration applies to a product with a maximum total weight of 3,4 kg/m². For the placing on the market of the product in the European Union/European Free Trade Association (EU/EFTA with the exception of Switzerland) Regulation (EU) No. 305/2011 *CPR* applies. The Declaration of Performance of the products taking into consideration *EN 14041* and the CE-marking of the products can be found on the manufacturer's technical information section.

Application

According to the use class as defined in *ISO 10874* the product can be used

- in domestic areas, classified as use class 23,
- in commercial areas, classified as use class 33 and 43

Technical Data

Constructional data

Name	Value	Unit
Grammage	3,4	kg/m ²
Product Form	Rolls of 2 m width or planks of several dimensions	-

Additional product properties in accordance with *EN 16776* and performance data of the product in accordance with the

Declaration of Performance with respect to its Essential Characteristics according to *EN 14041* can be found on the manufacturer's technical information section (www.wineo.de)

Base materials/Ancillary materials

Name	Value	Unit
Polyurethane including 53% renewable material	31,4	%
Inorganic Filler	62,8	%
Paper	1,4	%
Glass fibre	1,7	%
Organic materials	2,4	%
Additives	0,4	%

The specific product covered by the EPD contains substances listed in the *ECHA candidate list* (14.06.2023) or other carcinogenic, mutagenic or reprotoxic (CMR) substances in categories 1A or 1B which are not on the candidate list exceeding 0.1 percentage by mass: no

Reference service life

A calculation of the reference service life according to *ISO 15686* is not possible. The service life of resilient floor coverings depends on the correct installation taking into account the declared use classification and the adherence to cleaning and maintenance instructions. A minimum service life of 20 years can be assumed *BNB*, technical service life can be considerably longer.

LCA: Calculation rules

Declared Unit

Name	Value	Unit
Declared unit	1	m ²
Grammage	3.4	kg/m ²
Layer thickness	0.002	m
Gross density	1700	kg/m ³

The declared unit refers to 1 m² produced floor covering. The output of module A5 'Assembly' is 1 m² installed floor covering.

System boundary

Type of EPD: Cradle-to-grave

System boundaries of modules A, B, C, D:

A1-A3 Production:

Energy supply and production of the basic material, auxiliary material, transport of the material to the manufacturing site, emissions, waste water treatment, packaging material and waste processing up to the landfill disposal of residual waste (except radioactive waste). Benefits for generated electricity and steam due to the incineration of production waste are aggregated.

A4 Transport:

Transport of the packed floor covering from factory gate to the place of installation.

A5 Installation:

Installation of the floor covering, processing of installation waste and packaging waste up to the landfill disposal of residual waste (except radioactive waste), the production of the amount of floor covering that occurs as installation waste including its transport to the place of installation. Generated electricity and steam due to the incineration of waste are listed in the result table as exported energy. Preparing of the floor and adhesives are beyond the system boundaries and not taken into account.

B1 Use:

Indoor emissions during the use stage. After the first year, no product-related volatile organic compound (VOC) emissions are relevant due to the VOC decay curves of the product.

B2 Maintenance:

Cleaning of the floor covering for a period of 1 year: Wet cleaning – water consumption, production of the cleaning agent, waste water treatment. The declared values in this module have to be multiplied by the assumed service life of the floor covering in the building in question (see annexe, chapter 'General information on use stage').

B3 - B7:

The modules are not relevant and therefore not declared.

C1 De-construction:

Energy consumption of the de-construction machine.

C2 Transport:

Transport of the floor covering waste to a landfill or to the

municipal waste incineration plant (MWI).

C3 Waste processing:

C3-1: Landfill disposal needs no waste processing.

C3-2: Impact from waste incineration (plant with $R1 > 0.6$), generated electricity and steam are listed in the result table as exported energy.

C3-3: Collection of the carpet waste for recovery in the cement industry, waste processing (granulating), transport to the cement plant, emissions from the incineration.

C4 Disposal:

C4-1: Impact from landfill disposal,

C4-2: The carpet waste leaves the system in module C3-2,

C4-3: The pre-processed carpet waste leaves the system in module C3-3

D Recycling potential:

Calculated benefits result from materials exclusive secondary materials (net materials).

D-A5: Benefits for generated energy due to incineration of packaging and installation waste (incineration plant with $R1 > 0.6$),

D-1: Benefits for generated energy due to landfill disposal of carpet waste at the end of life,

D-2: Benefits for generated energy due to incineration of carpet waste at the end-of-life (incineration plant with $R1 > 0.6$),

D-3: Benefits for saved fossil energy and saved inorganic material due to recovery of the carpet in a cement plant. (incineration plant with $R1 > 0.6$),

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Europe

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Background data are taken from the Sphera Manged LCA content database 2023.2. Remaining data gaps are filled with ecoinvent 3.9 database

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

Information on describing the biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic carbon content in product	0.424	kg C
Biogenic carbon content in accompanying packaging	0.011	kg C

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

The following information refer to the declared modules and are the basis for calculations or can be used for further calculations. The indicated values refer to the declared functional unit of all products with a total weight of 3,4 kg/m².

Transport to the construction site (A4)

Name	Value	Unit
Litres of fuel , diesel, truck EURO 0-6 mix	0.0094	l/100km
Litres of fuel , heavy fuel oil, ship	0.0009	l/100km
Transport distance truck	540	km
Transport distance ship	1600	km
Capacity utilisation (including empty runs) truck	55	%
Capacity utilisation (including empty runs) ship	70	%

Installation in the building (A5)

Name	Value	Unit
Material loss	0.102	kg

Coated packaging paper and installation waste are considered to be incinerated in a municipal waste incineration plant. Pure cardboard packaging waste is going to be recycled. Preparation of the floor and adhesives are not taken into account.

Maintenance (B2)

Indication per m² floor covering and per year. Depending on the application based on *EN ISO 10874*, the technical service life

recommended by the manufacturer and the anticipated strain on the floor by customers, the case-specific useful life can be established. The effects of Module B2 need to be calculated on the basis of this useful life in order to obtain the overall environmental impacts.

Name	Value	Unit
Maintenance cycle (wet wiping)	130	1/year
Water consumption (wet wiping)	0.0325	m ³
Cleaning agent (wet wiping)	0.325	kg

Further information on cleaning and maintenance see www.wineo.de

End of Life (C1-C4)

Three different end-of-life scenarios are declared and the results are indicated separately in module C. Each scenario is calculated as a 100 % scenario.

Scenario 1: 100 % landfill disposal

Scenario 2: 100 % municipal waste incineration (MWI) with $R1 > 0.6$

Scenario 3: 100 % recovery in the cement industry

If combinations of these scenarios have to be calculated this should be done according to the following scheme:

If combinations of these scenarios have to be calculated this should be done according to the following scheme:

EOL-impact = x % impact (Scenario 1)

+ y % impact (Scenario 2)

+ z % impact (Scenario 3)

with x % + y % + z % = 100 %

Name	Value	Unit
Collected as mixed construction waste (scenario 1 and 2)	3.4	kg
Collected separately waste type (scenario 3)	3.4	kg
Landfilling (scenario 1)	3.4	kg
Energy recovery (scenario 2)	3.4	kg
Energy recovery (scenario 3)	1,208	kg
Recycling (scenario 3)	2.192	kg

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Recovery potentials due to the two end-of-life scenarios (module C) are indicated separately.

Recycling in the cement industry (scenario 3):

The organic material of the floor covering is used as an alternative fuel in a cement kiln. It mainly substitutes for lignite (68.8 %), hard coal (23.6 %) and petrol coke (7.6 %). The inorganic material is substantially integrated into the cement clinker and substitutes for the original material input. VDZ e.

LCA: Results

The results are valid for the declared product with a maximum total weight of 3,4 kg/m².

The declared result figures in module B2 have to be multiplied by the assumed service life (in years) of the floor covering in the building under consideration. Information on un-declared modules: Modules B3 - B7 are not relevant during the service life of the floor covering and are therefore not declared. Modules C3/1, C4/2 and C4/3 cause no additional impact (see "LCA: Calculation rules") and are therefore not declared. Module C2 represents the transport for scenarios 1 and 2. Column D represents module D/A5.

Version number of the characterisation factors used : EN 15804+A2 (based on EF 3.1)

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	X	X	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 m² floorcovering

Parameter	Unit	A1-A3	A4	A5	B1	B2	C1	C2	C3	C3/1	C3/2	C3/3	C4	C4/1	C4/2	C4/3	D	D/1	D/2	D/3
GWP-total	kg CO ₂ eq	2.76E+00	2.56E-01	2.5E-01	0	1.51E+00	0	1.39E-02	ND	ND	3.6E+00	3.65E+00	ND	1.79E+00	ND	ND	-2.44E-02	0	-8.15E-01	-2.43E-01
GWP-fossil	kg CO ₂ eq	4.33E+00	2.53E-01	1.97E-01	0	7.82E-01	0	1.38E-02	ND	ND	1.98E+00	2.03E+00	ND	2.31E-01	ND	ND	-2.43E-02	0	-8.11E-01	-2.43E-01
GWP-biogenic	kg CO ₂ eq	-1.7E+00	5.11E-04	4.87E-02	0	1.75E-02	0	3.23E-05	ND	ND	1.62E+00	1.62E+00	ND	1.56E+00	ND	ND	-1.09E-04	0	-3.64E-03	1.81E-04
GWP-luluc	kg CO ₂ eq	1.37E-01	1.84E-03	4.19E-03	0	7.09E-01	0	1.31E-04	ND	ND	2.14E-04	5.42E-04	ND	1.93E-04	ND	ND	-1.56E-06	0	-5.21E-05	-1.63E-04
ODP	kg CFC11 eq	7.15E-08	2.14E-14	2.14E-09	0	1.23E-07	0	1.23E-15	ND	ND	2.14E-13	4.98E-13	ND	3.93E-13	ND	ND	-1.86E-13	0	-6.19E-12	-5.91E-13
AP	mol H ⁺ eq	3.87E-02	3.2E-03	1.31E-03	0	2.11E-03	0	8.67E-05	ND	ND	1.87E-03	2.11E-03	ND	7.01E-04	ND	ND	-3E-05	0	-1E-03	-8.15E-04
EP-freshwater	kg P eq	1.21E-03	7.39E-07	3.63E-05	0	2.68E-05	0	5.14E-08	ND	ND	7.08E-07	8.93E-07	ND	4.5E-05	ND	ND	-3.84E-08	0	-1.28E-06	-3.61E-07
EP-marine	kg N eq	1.51E-02	1.09E-03	5.13E-04	0	5.46E-04	0	4.25E-05	ND	ND	8.65E-04	9.79E-04	ND	1.61E-04	ND	ND	-8.83E-06	0	-2.94E-04	-2.76E-04
EP-terrestrial	mol N eq	1.53E-01	1.2E-02	5.26E-03	0	8.13E-03	0	4.71E-04	ND	ND	9.86E-03	1.11E-02	ND	1.76E-03	ND	ND	-9.46E-05	0	-3.15E-03	-3.03E-03
POCP	kg NMVOC eq	1.33E-02	2.51E-03	5.43E-04	1.19E-05	3.01E-03	0	8.03E-05	ND	ND	2.24E-03	2.46E-03	ND	5.1E-04	ND	ND	-2.46E-05	0	-8.21E-04	-8.4E-04
ADPE	kg Sb eq	4.75E-06	1.35E-08	1.43E-07	0	7.17E-07	0	9.15E-10	ND	ND	1.55E-08	2.01E-08	ND	6.18E-09	ND	ND	-1.71E-09	0	-5.68E-08	-1.03E-08
ADPF	MJ	7.76E+01	3.42E+00	2.5E+00	0	1.38E+01	0	1.92E-01	ND	ND	2.1E+00	2.9E+00	ND	3.49E+00	ND	ND	-4.48E-01	0	-1.49E+01	-4.04E+01
WDP	m ³ world eq deprived	6.9E+01	2.39E-03	2.09E+00	0	3.38E-01	0	1.62E-04	ND	ND	5.14E-01	5.17E-01	ND	-3.3E-03	ND	ND	-2.25E-03	0	-7.5E-02	-2.93E-02

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 m² floorcovering

Parameter	Unit	A1-A3	A4	A5	B1	B2	C1	C2	C3	C3/1	C3/2	C3/3	C4	C4/1	C4/2	C4/3	D	D/1	D/2	D/3
PERE	MJ	1.62E+01	1.95E-01	1.22E+00	0	9.15E+00	0	1.36E-02	ND	ND	2.18E+01	2.2E+01	ND	3.15E-01	ND	ND	-1.27E-01	0	-4.23E+00	-3.87E-01
PERM	MJ	2.15E+01	0	-7E-02	0	0	0	0	ND	ND	-2.14E+01	-2.14E+01	ND	0	ND	ND	0	0	0	0
PERT	MJ	3.77E+01	1.95E-01	1.15E+00	0	9.15E+00	0	1.36E-02	ND	ND	3.89E-01	6.15E-01	ND	3.15E-01	ND	ND	-1.27E-01	0	-4.23E+00	-3.87E-01
PENRE	MJ	6.14E+01	3.43E+00	2.75E+00	0	1.38E+01	0	1.92E-01	ND	ND	1.8E+01	1.88E+01	ND	3.49E+00	ND	ND	-4.48E-01	0	-1.49E+01	-4.04E+01

PENRM	MJ	1.62E+01	0	-2.52E-01	0	0	0	0	ND	ND	-1.59E+01	-1.59E+01	ND	0	ND	ND	0	0	0	
PENRT	MJ	7.76E+01	3.43E+00	2.5E+00	0	1.38E+01	0	1.92E-01	ND	ND	2.1E+00	2.9E+00	ND	3.49E+00	ND	ND	-4.48E-01	0	-1.49E+01	-4.04E+01
SM	kg	2.15E-02	0	6.44E-04	0	0	0	0	ND	ND	0	0	ND	0	ND	ND	0	0	0	1.29E+00
RSF	MJ	0	0	0	0	0	0	0	ND	ND	0	0	ND	0	ND	ND	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	ND	ND	0	0	ND	0	ND	ND	0	0	0	0
FW	m ³	2.35E+00	2.15E-04	7.09E-02	0	9.78E-03	0	1.49E-05	ND	ND	1.22E-02	1.24E-02	ND	3.44E-05	ND	ND	-1.03E-04	0	-3.43E-03	-3.51E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2:

1 m² floorcovering

Parameter	Unit	A1-A3	A4	A5	B1	B2	C1	C2	C3	C3/1	C3/2	C3/3	C4	C4/1	C4/2	C4/3	D	D/1	D/2	D/3
HWD	kg	1.66E-08	1.23E-11	5.07E-10	0	1.51E-04	0	7.11E-13	ND	ND	2.73E-10	2.5E-10	ND	2.94E-10	ND	ND	-2.54E-11	0	-8.46E-10	-2.16E-12
NHWD	kg	1.79E-01	4.57E-04	3.55E-02	0	3.55E-02	0	2.77E-05	ND	ND	1E+00	1E+00	ND	3.39E+00	ND	ND	-2.19E-04	0	-7.29E-03	-2.16E-02
RWD	kg	1.3E-03	4.35E-06	4.17E-05	0	1.56E-04	0	2.48E-07	ND	ND	8.55E-05	1.37E-04	ND	4.13E-05	ND	ND	-3.37E-05	0	-1.12E-03	-6.86E-05
CRU	kg	0	0	0	0	0	0	0	ND	ND	0	0	ND	0	ND	ND	0	0	0	0
MFR	kg	0	0	0	0	0	0	0	ND	ND	0	1.29E+00	ND	0	ND	ND	0	0	0	0
MER	kg	0	0	0	0	0	0	0	ND	ND	0	0	ND	0	ND	ND	0	0	0	0
EEE	MJ	0	0	1.12E-01	0	0	0	0	ND	ND	3.73E+00	0	ND	0	ND	ND	0	0	0	0
EET	MJ	0	0	2.13E-01	0	0	0	0	ND	ND	7.1E+00	3.73E+01	ND	0	ND	ND	0	0	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:

1 m² floorcovering

Parameter	Unit	A1-A3	A4	A5	B1	B2	C1	C2	C3	C3/1	C3/2	C3/3	C4	C4/1	C4/2	C4/3	D	D/1	D/2	D/3
PM	Disease incidence	3.51E-07	4.31E-08	1.22E-08	0	2.4E-07	0	5.45E-10	ND	ND	1.37E-08	1.53E-08	ND	6.8E-09	ND	ND	-2.55E-10	0	-8.48E-09	-2.59E-08
IR	kBq U235 eq	5.04E-01	6.27E-04	1.55E-02	0	4.14E-02	0	3.58E-05	ND	ND	1.3E-02	2.16E-02	ND	6.11E-03	ND	ND	-5.6E-03	0	-1.87E-01	-6.59E-03
ETP-fw	CTUe	3.32E+01	2.41E+00	1.11E+00	1.02E-04	5.72E+00	0	1.35E-01	ND	ND	1.08E+00	1.51E+00	ND	2.98E+00	ND	ND	-6.09E-02	0	-2.03E+00	-1.52E+01
HTP-c	CTUh	2.82E-09	4.78E-11	8.77E-11	0	2.19E-09	0	2.73E-12	ND	ND	5.24E-11	6.39E-11	ND	1.53E-10	ND	ND	-4.92E-12	0	-1.64E-10	-6.78E-11
HTP-nc	CTUh	1.5E-07	1.99E-09	4.65E-09	7.4E-13	2.47E-08	0	1.2E-10	ND	ND	2.82E-09	3.19E-09	ND	1.22E-08	ND	ND	-1.22E-10	0	-4.08E-09	-2.55E-09
SQP	SQP	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

No substantiated values can be given for the SQP indicator with the existing database.

The result figures given in module B2 refer to a period of 1 year because a reference service life is not declared. They have to be multiplied by the assumed service life (in years) of the floor covering in the building under consideration.

Disclaimer 1 – for the indicator 'Potential Human exposure efficiency relative to U235'. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators 'abiotic depletion potential for non-fossil resources', 'abiotic depletion potential for fossil resources', 'water (user) deprivation potential, deprivation-weighted water consumption', 'potential comparative toxic unit for ecosystems', 'potential comparative toxic unit for humans – cancerogenic', 'Potential comparative toxic unit for humans - not cancerogenic', 'potential soil quality index'. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

The CO₂ uptake during the growth phase of renewable materials in the product is 1,55 kg. This amount is stored in the material as

biogenic carbon. At the end of life the stored carbon is released into the air again as 1,55 kg CO₂ emissions.

References

ISO 10874

DIN EN ISO 10874: 2012-04: Resilient, textile and laminate floor coverings - Classification

EN 13501-1

DIN EN 13501-1:2010-01: Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

ISO 14025

DIN EN /ISO 14025:2011-10/, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

EN 14041

DIN EN 14041: 2008-05: Resilient, textile and laminate floor coverings - Essential characteristics

EN 15804

DIN EN 15804:2012+A2:2019 + AC:2021, Sustainability of construction works —

Environmental Product Declarations — Core rules for the product category of construction products

ISO 15686

ISO 15686: Buildings and constructed assets - Service life planning

ISO 15686-1: 2011-05: Part 1: General principles and framework

ISO 15686-2: 2012-05: Part 2: Service life prediction procedures

ISO 15686-7: 2006-03: Part 7: Performance evaluation for feedback of service life data from practice

ISO 15686-8: 2008-06: Part 8: Reference service life and service-life estimation

EN 16776

DIN EN 16776: 2016-09: Resilient floor coverings - Heterogeneous polyurethane floor coverings - Specification

EN 16810

DIN EN16810: 2017-08: Resilient, textile and laminate floor coverings – Environmental product declarations – Product category rules

PCR Part A

Product Category Rules for Building-Related Products and Services Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report according to EN 15804+A2:2019, V1.3, Berlin: Institut Bauen und Umwelt e.V. (IBU), August 2022

PCR Part B

Product Category Rules for Building-Related Products and Services Part B: Requirements on the EPD for floor coverings, Berlin: Institut Bauen und Umwelt e.V. (IBU), August 2021

General Instructions for the IBU-EPD Program

General Instructions for the EPD-Program of the Institut Bauen und Umwelt e.V., The Preparation of Environmental Product Declarations - EPDs, version 2.0, Institut Bauen und Umwelt e.V., Berlin, January 2021, www.ibu-epd.de

CPR

Construction Products Regulation, Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011

BNB

Bundesministerium des Innern, für Bau und Heimat, 'Nutzungsdauern von Bauteilen zur Lebenszyklusanalyse nach BNB, 2017' des Bundesinstitut für Bau-, Stadt- und Raumforschung (BBSR)

REACH

Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency (ECHA), European Union Regulation No 1907/2006, June 2017,

Sphera Software and database

LCA for experts Software-System and Database for Life Cycle Engineering, Sphera Solutions Inc., Stuttgart, 2023-2

ecoinvent 3.9

ecoinvent, Zurich, Switzerland, Database Version 3.9, Dezember 2022



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the Life Cycle Assessment

Gemeinschaft umweltfreundlicher Teppichboden
(GUT) e.V.
Schönebergstraße 2
52068 Aachen
Germany

+45 (0)241 96843 410
mail@gut-ev.de
www.gut-ev.org



Owner of the Declaration

Windmüller GmbH
Nord-West-Ring 21
32832 Augustdorf
Germany

+49 (0)5237 609 0
info@windmoeller.de
www.windmoeller.de